SAFETY DATA SHEET

Limestone

Section 1. Identification

GHS product identifier : Limestone

Other means of identification : Limestone, Fine Grind, Pulverized Limestone

Identified uses : Used in the manufacture of bricks, mortar, cement, plasters, paving materials, glass,

shingles, joint compound, paint, flux.

Used as a mineral supplement for agricultural purposes, rock dust, fertilizer, and feed.

Supplier's details : Pete Lien & Sons, Inc.

PO Box 440

Rapid City, SD 57702

Emergency telephone : (605) 342-7224 (Monday-Friday 8am-5pm)

number (hours of operation)

Section 2. Hazards identification

Classification of the : SKIN IRRITATION – Not Classified substance or mixture EYE DAMAGE – Not Classified

SPECIFIC TARGET ORGAN TOXICITY SINGLE EXPOSURE [Respiratory System] - Category 2

Repeated Exposure

CARCINOGEN - Category 1A

GHS label elements



Hazard pictograms :

Signal word : Danger

Hazard statements : May cause cancer through inhalation. Causes damage to lungs through prolonged and

repeated exposure.

Precautionary statements

Prevention : Obtain special instruction before use. Do not handle until all safety precautions have been

read and understood. Wear protective gloves/protective clothing/eye protection/face

protection.

Response : If exposed or concerned: Get medical advice/attention.

Storage : Restrict or control access to stockpile areas. Engulfment hazard: To prevent burial or

suffocation, do not enter a confined space, such as a silo, bulk truck or other storage container or vessel that stores or contains aggregates without an effective procedure for assuring safety.

Disposal: Dispose of contents/containers in accordance with applicable regulations.

Hazards not otherwise: None known

classified

Ingredients with : Not Applicable

unknown toxicity

Supplemental Information:

Respirable Crystalline Silica (RCS) may cause cancer. Limestone is a naturally occurring mineral complex that contains varying quantities of quartz (crystalline silica). In its natural bulk state, limestone is not a known health hazard. Limestone may be subject to various natural or mechanical forces that produce small particles (dust) which may contain respirable crystalline silica (particles less than 10 micrometers in aerodynamic diameter). Repeated inhalation of respirable crystalline silica (quartz) may cause lung cancer according to IARC and NTP; ACGIH states that it is a suspected cause of cancer. Other forms of RCS (e.g., tridymite and cristobalite) may also be present or formed under certain industrial processes.

Section 3. Composition/information on ingredients

Substance/mixture : Calcium Carbonate

CAS number/other identifiers

Component CAS # % by weight

Calcium Carbonate 1317-65-3 >50
Crystalline Silica (quartz) 14808-60-7 >0.1

Impurities : Small quantities of calcium carbonate, calcium oxide and impurities. Impurities will vary from

source to source.

Section 4. First aid measures

Description of necessary first aid measures

Eye Contact: Contact can cause irritation of eyes. Immediately flush eyes with generous amounts of water for at

least 15 minutes. Pull back the eyelid to ensure that all limestone dust has been washed out. Seek

medical attention if irritation develops or persists.

Skin Contact: Wash exposed area with soap and water. Seek medical attention if irritation develops and persists.

Ingestion: Rinse mouth and drink plenty of water. Never give anything by mouth to an unconscious person. Get

medical attention.

Inhalation: Move to fresh air. Seek medical attention if symptoms develop or persist.

<u>Most important symptoms/effects, acute and delayed</u>: Long-term exposure by inhalation may cause permanent damage. This product contains crystalline silica, which has been classified by IARC as (Group I) carcinogenic to humans when inhaled. Inhalation of silica can also cause a chronic lung disorder, silicosis.

<u>Indication of immediate medical attention and special treatment needed, if necessary:</u> See first aid information above. Note to Physicians: Provide general supportive measures and treat symptomatically.

Section 5. Fire-fighting measures

Extinguishing Media: Substance is nonflammable; use agent most appropriate to extinguish surrounding fire.

Unsuitable Extinguishing Media: None known

Fire Hazards : No unusual fire or explosion hazards noted. Not a combustible dust.

Hazardous Combustion Products: Calcium Oxides

Special Protective Equipment and Fire Fighting Instructions:

Use protective equipment and appropriate for surrounding materials. Contact with powerful oxidizing agents may cause fire and/or explosions.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Spill/Leak Procedures : Use proper protective equipment and clothing during clean-up of materials that contain or may

liberate limestone dust.

Spilled material where, where dust is generated, may overexpose cleanup personnel to respirable crystalline silica-containing dust. Avoid generating dust. Do not clean up with compressed air or dry sweep. Wetting of spilled material and/or use of respiratory protective

equipment may be necessary

Methods and materials for containment and cleaning up

Containment : For large spills, as much as possible, avoid the generation of dusts. Prevent release to sewers

or waterways.

Section 7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Avoid dust formation or accumulation.

Section 8. Exposure controls/personal protection

Exposure limits

Component CAS # Exposure limits

Calcium Carbonate 1317-65-3 OSHA PEL: 5mg/m³ (respirable)

NIOSH TWA: 5mg/m³ (respirable)

Crystalline Silica 14808-60-7 OSHA PEL: 10mg/m³ divided by (the percentage of silica in the

dust plus 2) (respirable)

ACGIH TLV: 0.025 mg/m³ (respirable)

Engineering controls: Provide ventilation adequate to maintain PELs. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.

Individual Protection Measures

Respiratory Protection: Use NIOSH/MSHA approved respirators if airborne concentration exceeds PEL.

Skin Protection : Use appropriate personal protective equipment as required.

Eye Protection : Use safety glasses with side shields or safety goggles.

Other : Eye wash fountain and emergency showers are recommended

Thermal Hazards: Not Anticipated. Wear appropriate thermal protective clothing, when necessary.

General Hygiene : Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

Section 9. Physical and chemical properties

Physical State : Solid

Appearance : White, tan, pink or grayish-white material

Odor : Not applicable
Odor threshold : Not applicable

pH at 25 degrees C : 8-10

Melting point : Not applicable
Initial boiling point : Not applicable
Flash point : Non-combustible
Evaporation rate : Not applicable
Flammability (solid, gas) : Not applicable
Lower and upper explosive : Not applicable

(flammable) limits

Vapor pressure : Not applicable
Vapor density : Not applicable
Relative density : 2.6-2.8 g/cc
Solubility in water : Insoluble

Partition coefficient: n : Not applicable

octanol/water

Auto-ignition temperature : Not applicable
Decomposition temperature : Not applicable
Viscosity : Not applicable

Section 10. Stability and reactivity

Reactivity: This product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability: Material is stable under normal conditions

Possibility of : No dangerous reaction known under conditions of normal use.

hazardous reactions

Conditions to avoid : Acids. Ignites with fluorine.

Incompatible materials: Incompatible with ammonium salts and magnesium

decomposition

products

Section 11. Toxicological Information

Information on the likely routes of exposure: See First Aid discussion above.

Inhalation :Repeated inhalation of respirable crystalline silica (quartz) may cause silicosis, a fibrosis

(scarring) of the lungs. Silicosis is irreversible and may be fatal. Silicosis increases the risk of contracting pulmonary tuberculosis. Some studies suggest that repeated inhalation of respirable crystalline silica may cause other adverse health effects including lung and kidney

cancer.

Skin Contact :Limestone dust may cause irritation through mechanical abrasion

Eye Contact : Limestone dust may cause irritation through mechanical abrasion

Ingestion : Not likely, due to form of the product. However, accidental ingestion of the content may cause

discomfort

Symptoms related to the physical, chemical and toxicological characteristics: Limestone dust: Discomfort in chest.

Shortness of breath, Coughing.

Delayed and immediate effects and also chronic effects from exposure: Not expected to be acutely toxic. This product is not expected to be a skin hazard. Direct contact with eyes may cause temporary irritation. No respiratory sensitizing effects known. Not known to be a dermal irritant or sensitizer. No data available to indicate product or any component present at greater than 0.1% are mutagenic or genotoxic.

Numerical measures of toxicity: No LD50/LC50 have been identified for this product's components.

Carcinogen listing: Limestone is not listed by MSHA, OSHA, or IARC as a carcinogen, but this product contains crystalline silica, which has been classified by IARC as (Group I) carcinogenic to humans when inhaled

Section 12. Ecological information

Ecotoxicity : There is no data available. **Persistence and degradability**: There is no data available.

Bioaccumulative potential: This material shows no bioaccumulation effects of food chain concentration toxicity.

Mobility in soil : There is no data available.

Other adverse effects: This material is alkaline and if released into water or moist soil will cause an increase in pH.

Section 13. Disposal considerations

Disposal Instructions : Do not allow fine particulate matter to drain into sewers/water supplies. Do not

contaminate ponds waterways or ditches with fine particulates. Dispose of contents in

accordance with local/regional/national/international regulations.

Hazardous waste code : Not regulated

Waste from residues/ :Dispose of in accordance with local regulations. Empty containers or liners may retain

unused product some product residues. This material and its container must be disposed of in a safe

manner (See disposal instructions)

Contaminated packaging : Since emptied containers may retain product residue, follow label warnings even after

container is emptied. Empty packaging materials should be recycled or disposed of in

accordance with applicable regulations and practices.

Section 14. Transport information

DOT :Not regulated as dangerous goodsIATA :Not regulated as dangerous goodsIMDG :Not regulated as dangerous goods

Transport in bulk according to: Not applicable

Annex II of MARPOL 73/78

and the IBC Code

Section 15. Regulatory information

US Federal Regulations :This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)-Not Regulated OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050-Not Listed

CERCLA Hazardous Substance List (40 CFR 302.4)-Not Listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories Immediate Hazard- No

Delayed Hazard- Yes
Fire Hazard- No
Pressure Hazard- No
Reactivity Hazard- No

SARA 302 Extremely hazardous substance-Not Listed

SARA 311/312 Hazardous chemical-Yes SARA 313 (TRI reporting)-Not regulated

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List-Not regulated Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)-Not regulated Safe Drinking Water Act (SDWA)-Not regulated

Section 16. Other information

History

Date of issue (mm/dd/yyyy) : 06/01/2015

Version : 1

Disclaimer: The information contained in this document applies to this specific material as supplied. Pete Lien & Sons, Inc. believes that the information contained in this SDS is accurate. The suggested precautions and recommendations are based on recognized good work practices and experience as of the date of publication. They are not necessarily all-

inclusive or fully adequate in every circumstance as not all use circumstances can be anticipated. The suggestions should not be confused with nor followed in violation of applicable laws, regulation, rules or insurance requirement.

It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for one's own particular use. Since the actual use of the product described herein is beyond our control, Pete Lien & Sons, Inc., assumes no liability arising out of the use of the product by others. Appropriate warnings and safe handling procedures should be provided to handlers and users. Product must not be used in a manner which could result in harm.